

Cattle Marking Paint

Issue Date: Apr 2018
Reference: 06CMP
Page 1 of 2

Product Description	A weather resistant, non-toxic coating for the marking of cattle and sheep.				
Features & Use	<ul style="list-style-type: none"> • A specially developed treatment for cattle and sheep to identify the ownership of particular animals • Coating can be easily removed during hide or fleece washing processes. 				
Approvals/ Certification	Please consult Axalta Coating Systems				
Finish	Slight gloss				
Volume Solids	58 ± 2% (varies with colour)				
VOC Content	325 ± 20 g/litre (varies with colour)				
Film Thickness Range And Coverage		Dry Film Thickness	Wet Film Thickness	Theoretical Coverage	
	Typical	30 µm	52 µm	19.3 m ² /litre	
	Practical coverage depends on the application method, painting conditions and the shape and roughness of the surface to be coated				
Drying Times	Applied to 30 microns DFT	+10°C	+23°C	+35°C	
	Dust Free		2½ hr	1½ hr	45 min
	Hard Dry		7 hr	5 hr	4 hr
	Overcoating	Minimum Maximum	Usually a one coat application		
	Drying and recoating times are related to the film thickness, temperature, the relative humidity of the air and ventilation				
Colours	Blue, Red, Yellow, White, Light and Dark Green				
Product Code	06CMP				
SG	1.52 kg/lit (varies with colour)				
Storage Conditions	Store in dry, cool conditions and protect from frost				
Shelf Life	Minimum 12 months if stored as above in unopened containers				
Flash Point	23-60°C				



Cattle Marking Paint

Surface Preparation	<ul style="list-style-type: none"> Apply in dry conditions 				
Mixing	Must be mixed thoroughly preferably by using a mechanical agitator before use. Agitate periodically to ensure paint remains homogeneous.				
Thinner	Do not thin Equipment Cleaner No.3 Thinner				
Application Conditions	Do not apply in wet conditions				
Application Methods	Method	Airless Spray	Conventional Spray	Brush	Roller
		No	No	Yes	No
	<ul style="list-style-type: none"> Brush/roller application is recommended – use as supplied 				
Product Notes	<ul style="list-style-type: none"> Supplied in 2.5lt cans 				
Health & Safety	Containers are provided with safety labels which should be observed. Further information about hazardous influences and protection are detailed in individual Product Safety Data Sheets. A Safety Data Sheet for this product is available on request from Axalta Coating Systems.				

AN AXALTA COATING SYSTEMS BRAND



The information provided herein corresponds to our knowledge on the subject at the date of its publication. This information may be subject to revision as new knowledge and experience becomes available. The data provided fall within the normal range of product properties and relate only to the specific material designated; these data may not be valid for such material used in combination with any other materials or additives or in any process, unless expressly indicated otherwise. The data provided should not be used to establish specification limits or used alone as the basis of design; they are not intended to substitute for any testing you may need to conduct to determine for yourself the suitability of a specific material for your particular purposes. Since Axalta cannot anticipate all variations in actual end-use conditions Axalta makes no warranties and assumes no liability in connection with any of this information. Nothing in this publication is to be considered as a license to operate under or a recommendation to infringe any patent rights. This product is for professional use only.